

### For Use With Wire Rope Catalogue No 80

All sheaves fitted with bronze bush. Taper roller bearing available. Grease lubricated on sheave pin and headfitting. Painted finish. Galvanising optional at extra cost.



Fmm	F"	B	D
152	6	8-10	1
152	6	12-14	1 1/2
203	8	14-16	2
254	10	20-22	3
254	10	20-22	5
305	12	20-22	3
305	12	24-26	5
356	14	24-26	5
356	14	28-30	8
406	16	24-26	5
406	16	28-30	8
406	16	32-35	10
457	18	32-35	8
457	18	32-35	10

### For Use With Wire Rope Catalogue No 82/2

All sheaves fitted with bronze bush. Taper roller bearing available. Grease lubricated on sheave pin and headfitting. Painted finish. Galvanising optional at extra cost.



Fmm	F"	B	D
152	6	12-14	3
203	8	12-14	4
203	8	14-16	6
254	10	14-16	8
254	10	20-22	10
305	12	20-22	10
305	12	24-26	14
357	14	24-26	14
357	14	28-30	20
406	16	28-30	30
406	16	32-35	30
457	18	28-30	25
457	18	32-35	30

### For Use With Wire Rope Catalogue No 82/3

All sheaves fitted with bronze bush. Taper roller bearing available. Grease lubricated on sheave pin and headfitting. Painted finish. Galvanising optional at extra cost.



Fmm	F"	B	D
152	6	12-14	6
203	8	14-16	9
254	10	20-22	14
305	12	24-26	20
336	14	24-26	20
356	14	28-30	30
406	16	32-35	30
457	18	32-35	40

#### Key

F Sheave outside diameter

B Rope diameter

D Safe working loads in tonnes